

TITLE OF THE INVENTION

IMAGE PROCESSING APPARATUS, IMAGE FORMING APPARATUS,
AND IMAGE PROCESSING METHOD DEPENDING ON THE TYPE OF
ORIGINAL IMAGE

5 CROSS-REFERENCE TO RELATED APPLICATIONS

This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Applications No. 11-094981, filed April 1, 1999; and
No. 11-094982, filed April 1, 1999, the entire contents
10 of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

The present invention relates to an image
processing apparatus, an image forming apparatus, and
an image processing method for performing a specified
15 conversion process when filing or copying documents or
images.

In an image forming apparatus, color or
monochromatic images of color or monochromatic copier
or the like are read, and copy images are formed, and
20 when copying, a high image quality is required
regardless of the type of the original image.

The image quality of the image information
necessary to realize a high copy image quality differs
significantly depending on the type of the original to
25 be copied. For example, in the case of a photographic
original, reproduction of color and gradation is
important, and the image quality true to the original

is demanded. On the other hand, in the case of a document original mainly containing characters, the clarity is demanded rather than the color of characters, and an easy-to-read image quality is required.

5 In a conventional copier, however, original modes optimizing the quality of copy image in various originals are available (character/photo mode, character mode, photo mode, map mode and the like), and the user selects a proper original mode depending on
10 the type of the original to be copied, and copies the image. Herein, the character mode and photo mode are exclusive modes for character only and photo only, and in the case of a mixed original of character and photo, the character/photo mode is used. For example, this
15 sort of the image forming apparatus is disclosed in US patent application No. 08/682,007, in which the image processing apparatus can extinguish character area, a graph area, page area, and photo area from the image data, and it processes the image data corresponding to
20 the extinguished areas.

 However, discrimination of regions conducted by the apparatus is not always perfect in precision of discrimination, and wrong discrimination may occur, and therefore depending on the condition of image
25 processing, the image quality may deteriorate extremely in a falsely discriminated region, or when regions of same type are discriminated differently, the image

quality differs in the boundary of the two regions. To decrease problems due to such wrong discrimination, the difference in processing is reduced between the image types to be discriminated, and in the case of wrong
5 discrimination, deterioration of image quality due to wrong discrimination may be made less obvious, but when the difference in processing between plural image types to be discriminated is reduced, the degree of improvement of image quality when discriminated
10 correctly is smaller, and therefore the image quality when the original of characters only is, for example, formed in character/photo mode is inferior to the case when formed in character mode if discriminated correctly. Hence, more accurate discriminating
15 capability of image types of original is demanded, and the image processing apparatus capable of processing the image accordingly is required.

BRIEF SUMMARY OF THE INVENTION

It is an object of the present invention to
20 present an image processing apparatus, an image forming apparatus, and an image processing method capable of discriminating the types of original images correctly, and processing the images most efficiently suited to the type of the original image.

25 The present invention provides an image processing apparatus comprising input means for inputting image data of an original image; discriminating means for

extracting a predetermined region by using a feature of pixel of the image data input from the input means, and for discriminating the attribute of the region; determining means for determining the type of the image data on the basis of the distribution of the regions attribute of which discriminated by the discriminating means; and processing means for processing the image data as specified depending on the type of the image data determined by the determining means.

With such constitution, the present invention discriminates attributes of image types in plural regions, and determines the image type of the entire document image on the basis of the distribution of the discriminated attributes. As a result, the image types can be determined more accurately, and correct processing is done securely depending on the image type of the document, so that an image processing apparatus capable of obtaining image data with high image quality can be presented.

The present invention further provides an image forming apparatus comprising input means for inputting image data of an original image; discriminating means for extracting a predetermined region by using a feature of pixel of the image data input from the input means, and for discriminating the attribute of the region; determining means for determining the type of the image data on the basis of the distribution of the

regions attribute of which discriminated by the discriminating means; processing means for processing the image data as specified depending on the type of the image data determined by the determining means; and
5 image forming means for forming an image on a recording medium on the basis of the image data processed as specified by the processing means.

In the present invention, as described above, in the image processing apparatus and image forming
10 apparatus, optimum image processing is done depending on the type of the document image by the same principle of operation, so that image data and image are formed at high image quality.

Additional objects and advantages of the invention
15 will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and
20 combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the
25 invention, and together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the

principles of the invention.

FIG. 1 is a block diagram showing a schematic constitution of an image processing apparatus in a first embodiment of the present invention;

5 FIG. 2 is a flowchart for explaining an example of image processing in the image processing apparatus in the first embodiment;

10 FIG. 3 is a flowchart for explaining the image type determining process in the image processing apparatus in the first embodiment;

FIG. 4 is a flowchart for explaining the image type determining process in the image processing apparatus in the first embodiment;

15 FIG. 5 is a flowchart for explaining the data converting process in the image processing apparatus in the first embodiment;

FIG. 6 is a block diagram showing a schematic constitution of an image processing apparatus in a second embodiment of the present invention;

20 FIG. 7 is a flowchart for explaining an example of image processing in the image processing apparatus in the second embodiment;

25 FIG. 8 is a flowchart for explaining the image correcting process in the image processing apparatus in the second embodiment;

FIG. 9 is a block diagram showing a schematic constitution of an image processing apparatus in a

third embodiment of the present invention;

FIG. 10 is a flowchart for explaining an example of image processing in the image processing apparatus in the third embodiment;

5 FIG. 11 is a flowchart for explaining the image type changing process in the image processing apparatus in the third embodiment;

10 FIG. 12 is a block diagram showing a schematic constitution of an image processing apparatus in a fourth embodiment of the present invention;

FIG. 13 is a flowchart for explaining an example of image processing in the image processing apparatus in the fourth embodiment;

15 FIG. 14 is a flowchart for explaining the application starting process in the image processing apparatus in the fourth embodiment;

FIG. 15 is a block diagram showing a schematic constitution of an image forming apparatus in a fifth embodiment of the present invention;

20 FIG. 16 is a diagram showing an example of constitution of image processing means;

FIG. 17 is a diagram showing an example of circuit constitution of color converting means;

25 FIG. 18 is a diagram showing an example of circuit constitution of space filter means;

FIG. 19 is a diagram showing a filter constitution;

FIG. 20 is a diagram showing a specific example of circuit constitution of space filter means;

FIG. 21 is a diagram showing an example of circuit constitution of black printing means;

5 FIG. 22 is a diagram showing an example of constitution of γ -correcting means;

FIG. 23 is a diagram for explaining setting of density converting curve;

10 FIG. 24 is a diagram showing constitution of binary processing by error diffusion method;

FIGS. 25A, 25B are diagrams for explaining gradation processing means;

FIG. 26 is a diagram showing an example of constitution of page information discriminating means;

15 FIG. 27 is a diagram showing an example of constitution of image forming apparatus when using page discriminating information and rectangle discriminating information according to a sixth embodiment;

20 FIGS. 28A to 28D are diagrams for explaining page discriminating information and original mode;

FIG. 29 is a diagram showing an example of constitution of image processing means for executing image processing by discriminating in pixel unit according to a seventh embodiment;

25 FIG. 30 is a diagram showing an example of circuit constitution of pixel unit discriminating means;

FIG. 31 is a diagram for explaining a window of

4×4;

FIG. 32 is a diagram showing an example of constitution of image forming apparatus when using page discriminating information by pixel unit discriminating means according to an eighth embodiment;

FIG. 33 is a diagram showing an example of constitution of image forming apparatus when becoming impossible to discriminate according to a tenth embodiment;

FIG. 34 is a diagram showing an example of constitution of image forming apparatus when becoming impossible to discriminate according to an eleventh embodiment;

FIG. 35 is a diagram showing other example of constitution of image forming apparatus when using page discriminating information according to a twelfth embodiment; and

FIG. 36 is a diagram showing the relation of original mode expressing the operation mode, page discriminating information, and processing condition of each image processing block.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings, embodiments of the present invention are described in detail below.

<First Embodiment>

A first embodiment of the present invention is described below. FIG. 1 shows a schematic constitution

of an image processing apparatus according to the first embodiment of the present invention. In FIG. 1, the image processing apparatus comprises an image input unit 101, a region discriminating unit 102, an image type determining unit 103, a data converting unit 104, and an image forming unit 105.

The image input unit 101 is a device for inputting image data, and by an image input device such as image scanner or a device for reading a document and converting into image data, this is a device for incorporating what is depicted from document or other paper. The image input unit of the present invention may be composed of a reading device such as image scanner, or a device for incorporating image already stored in a filing device or the like as image data.

The region discriminating unit 102 is to discriminate a pixel having character as a region from the image data input from the image input unit 101. First, the image data input in the image input unit 101 is separated into a plurality of binary image data depending on the density difference of peripheral pixels, chroma and other state, and divided and extracted into each region where the character or pattern is coupled physically or logically from the image, and feature quantities such as the position of the reason, its size, shape, structure and density distribution are measured, and the attribute is

determined as the document element. Attribute types of document elements include character, photograph, drawing, table, and dots.

5 Some specific techniques for separating into a plurality of binary image data can be used. In this case, as the output of the image separating unit 102, seven pieces of binary separate image data are created, that is, character image, half tone image, background image, dot image, color image, gray image, and black
10 image. These techniques are already known.

Some specific techniques for extracting and for discriminating documents elements may be used.

In the region discriminating region 102, not only from single image data, feature quantities of a
15 plurality of image data are integrated according to a rule, and the region attribute of the input image data is determined. For example, from both character image and half tone image, when regions are extracted at the same position, the type of the region and the size of
20 the region are determined. For example, when a photo region is present on the character image, and a half tone image and a half tone pixel are present at a same position, it is determined as a continuous gradation photo region. Some specific techniques for determining
25 the region attribute from plural pieces of image data are already known, and may be used.

The image type determining unit 103, of which

detail is described below, determines feature quantities such as presence or absence of key regions such as dot and photograph, and complicatedness as document structure depending on the degree of overlapping of rectangular regions, from the results discriminated in each region such as character, photograph, drawing, table and dot in the region discriminating unit 102, and determines what kind of document is the input image data.

10 Herein, types of image data include, for example:

1) The background is uniform, and only characters, drawings and tables are present.

2) The background has dots, and only characters, drawings and tables are present.

15 3) Only dot photograph is present.

4) Only continuous photograph is present.

5) At least one of characters, drawings and tables coexists with dot photograph, and also it is possible to extract a rectangular region; or at least one of characters, drawings and tables coexists with continuous photograph, and also it is possible to extract a rectangular region.

20 6) At least one of characters, drawings and tables coexists with dot photograph, and it is impossible to extract a rectangular region; or at least one of characters, drawings and tables coexists with continuous photograph, and it is impossible to extract

a rectangular region.

5 The data converting unit 104, of which detail is described later, changes the type of input image data according to the type of the document corresponding to the type of image determined in the image type determining unit 103. Change of type of image data may be, for example, change of resolution, compression rate, or number of colors. Also, the region information of attribute may be converted into an image.

10 The image forming unit 105 is to form an image of image data converted by the data converting unit 104 on a recording medium such as a sheet. At this time, further, it may be also saved in a storage as image file.

15 In such constitution, processing of the image processing apparatus of the present invention is described below.

20 FIG. 2 is a flowchart showing an example of document processing procedure in the image processing apparatus shown in FIG. 1. Referring to this flowchart, flow of processing of the image processing apparatus of the present invention is described below.

25 First, a document image is taken into the image input unit 101 (step ST201). That is, using an image input device such as scanner, the image is read from the documents, or a filing system or the like containing image file data is converted into image data

by the image input unit 101.

In the region discriminating region 102, reading out one line or several lines from the image input device, data is divided into a plurality of binary image data depending on the state of each pixel such as density difference of peripheral pixel or chroma, and divided and extracted in each region in which the character or pattern is coupled physically or logically, and the type of region and degree of importance are discriminated by measuring the feature quantities such as the position of the region, its size, shape, structure and density distribution, thereby extracting character, photograph, drawing, table and dot regions (step ST202). This operation is repeated until processing of all pixels of the input image is over (step ST203).

After all pixel attributes are determined, in the image type determining unit 103, from the results discriminated in each region of character, photograph, drawing, table and dot, by determining the feature quantities such as presence or absence of key regions such as dot and photograph, and complicatedness as document structure from the degree of overlapping of rectangular regions, it is determined what kind of document is the input image data (step ST204). The detail of specific processing in the image type determining unit 103 is described later by referring to

FIG. 3.

After determining the type of the document of the input image data, in the data converting unit 104, the format of image data is converted depending on the document type according to the type of the image data (step ST205). The detail of specific processing in the data converting unit 104 is described later by referring to FIG. 5.

Finally, in the image forming unit 105, the image converted in the image data format is formed on a recording medium (step ST206).

This is a rough processing operation of the image forming apparatus. The processing of individual elements is described specifically below.

FIG. 3 is a flowchart showing the detail of image type determining process as an example in the image type determining unit 103 of the image processing apparatus, and this is a flowchart of the process corresponding to step ST204 shown in FIG. 2. The image type determining process is a process of what kind of document is the input image data, by making use of the region discriminating result of each pixel.

In this process, first, an example of document type classification determined by the type of image data is described below.

A uniform background original document is one not having photo region and dot region. It is therefore an

original of character region only or in a blank state in which nothing is written.

5 A dot background original is one having a dot region, and having a character region contained in the dot region.

A dot photo original is one having a dot region, and having photo region in the dot region but not having character region.

10 A continuous gradation photo original is one not having dot region and character region, and having photo region only.

15 A rectangular discrimination original does not belong to any one of uniform background original, dot background original, dot photo original, or continuous gradation photo original, and not having complicated layout structure, which can be divided into each region of character, dot, photograph, drawing, table, etc.

20 One having complicated layout structure, which cannot be divided into each region of character, dot, photograph, drawing, table and the like, is discriminated from other originals as an indiscriminative original.

25 In FIG. 3, pixel attribute data 151 is the attribute of each pixel of input image data determined by using the type and importance of the region of the plural image data discriminated in the region discriminating unit 102, and is expressed as the region

of each document element.

First, reading data from the pixel attribute data 151, it is checked if dot region is present or not (step ST301). If a dot region is present, then it is
5 checked if photo region is present or not (step ST302). If a photo region is present, then it is checked if character region is present or not (step ST303). If a character region is present, it is a rectangle discrimination candidate original 152. The rectangle
10 discrimination candidate original 152 is classified into rectangular discriminative original or indiscriminative original, consequently by the process for verification of complicatedness of the layout structure. A detailed description of this process is
15 given later by referring to FIG. 4.

If there is no character region at step ST303, it is a dot photo original 153.

If there is no photo region at step ST302, it is checked if character region is present in the dot
20 region or not (step ST304). If there is a character region in the dot region, it is a dot background original 154. If there is no character region in the dot region, it is further checked if there is character region outside the dot region (step ST305). If there
25 is no character region outside the dot region, it is a dot photo original 153. If there is a character region outside the dot region, it is a rectangle

discrimination candidate original 152.

If there is no dot region at step ST301, it is checked if photo region is present or not (step ST306). If there is no photo region, it is a uniform background original 156. If there is a photo region, it is further checked if character region is present or not (step ST307). If there is no character region, it is a continuous gradation photo original 155. If there is a character region, it is a rectangle discrimination candidate original 152.

By this process, the input image data is determined in any one of rectangle discrimination candidate original 152, dot photo original 153, dot background original 154, continuous gradation photo original 155, and uniform background original 156.

FIG. 4 is a flowchart showing the detail of image type determining process as an example in the image type determining unit 103 of the image processing apparatus of the present invention, which is a flowchart of process corresponding to the rectangle discrimination candidate original 152 shown in FIG. 3.

When determined to be a rectangle discrimination candidate original 152, the complicatedness of the layout structure is verified, and it is classified into rectangle discriminative original or indiscriminative original, and at this time, as an index of measuring the complicatedness of the layout structure, the degree

of overlapping of rectangular regions may be measured. The degree of overlapping of rectangles may be directly verified, but when the number of rectangular regions is increased, it is estimated that the number of times of comparison increases dramatically. Accordingly, by voting the rectangle size in the two-dimensional voting space being prepared, the degree of overlapping may be estimated from the state of the voting space (step ST401).

This voting space is for measuring the degree of overlapping of rectangular regions, and its resolution may be lower than the resolution of the original image. Voting is done by adding the feature such as rectangle size of the region to the position where the coordinate position of the rectangular region is converted into the coordinate position of the voting space. An example of rectangle size is width, height or area of the rectangle. Besides, the voting value may be weighted according to the attribute of the rectangular region, that is, the character, photograph, drawing, table, dot or other attribute. For example, the attribute having a great effect on the layout structure, such as photograph, drawing and table is provided with a large weight, and the character has a small weight, so that the voting value is large in the overlapped region of photograph or drawing and table. Considering the complicatedness of the layout structure,

overlapping of photograph or drawing and table is classified into a complicate category. Therefore, in this case, it is easy to regard as a complicated structure. For faster processing, moreover, it is also possible to limit the rectangular region to be voted. For example, a small character region does not always have a large effect in determination of layout structure. In such a case, by limiting the rectangle size to be voted, the number of times of voting is saved, and a faster processing is expected. However, if the character region existing in image data is composed of small character regions alone, it cannot be always ignored. In such a case, it is possible to adjust the limitation depending on the state of the pixel attribute data which is the output of the region discriminating unit 102.

When voting of rectangle size in all voting spaces is over, the feature quantities in the voting spaces are measured (step ST402). As the feature quantity, for example, the statistic value of maximum or variance may be used, or, regarding the voting space to be a multi-value image, the region may be extracted after binary processing. In the former case, it is possible to determine by comparison between the calculated value and the preset threshold, and in the latter case it is possible to determine by measuring the graphic feature of the extracted region. At step ST402, the former

example is employed. In this case, if the maximum (max) or variance (var) is smaller than the threshold (a) or (b), the layout structure is regarded not complicated, and is determined to be a rectangle
5 discriminative original 157, and if larger, to the contrary, the layout structure is regarded complicated, and is determined to be an indiscriminative original 158 (step ST403).

This is the detailed description of the image type
10 determining unit 103, and, as a result, the input image data is determined as any one of dot photo original 153, dot background original 154, continuous gradation photo original 155, uniform background original 156, rectangle discriminative original 157, and
15 indiscriminative original 158.

FIG. 5 is a flowchart showing the detail of data conversion process as an example in the data converting unit 104 of the image processing apparatus, which is a flowchart of the process corresponding to step ST205 in
20 FIG. 2. The data conversion process is a process for changing the format of the input image data by making use of the determining result of image type.

The image type information 161 is the output of the image type determining unit 103, and expresses the
25 type of input image data, which is one of dot photo original 153, dot background original 154, continuous gradation photo original 155, uniform background

original 156, rectangle discriminative original 157,
and indiscriminative original 158.

First, it is checked if the image type information
161 is an indiscriminative original or not (step ST501).

5 If not indiscriminative original, next it is checked if
rectangle discriminative original or not (step ST502).

In the case of rectangle discriminative original,
making use of the information of the pixel attribute
obtained in the region discriminating unit 102, the
10 data conversion process is executed on the input image
data in every rectangular region (step ST503).

Data conversion process is, for example, change of
resolution, compression rate, or number of colors. A
rule of data conversion process may be preset in every
15 pixel attribute, and the data conversion process may be
done according to this rule. For example, in the case
of dot photo region or continuous photo region, if the
resolution is lowered or the compression rate is raised,
image deterioration may not be obvious, and the
20 quantity of information can be curtailed. Or if only
black characters are present in the character region,
the multi-value data may be converted into two-value
data, so that the quantity of information can be
curtailed. In this way, by presetting a specific rule
25 of data conversion process in every pixel attribute, it
is possible to convert into efficient image data.

As a result of data conversion process, converted

image data 162 is output.

If it is not rectangle discriminative original at step ST502, the entire image is uniformly processed by data conversion (step ST504). As uniform data
5 conversion process, for example, in the case the image type information 161 is dot photo original or continuous gradation photo, if the resolution is lowered or the compression rate is raised, image deterioration may not be obvious, so that the quantity
10 of information may be curtailed. Or when the image type information 161 is uniform background original and there are only black characters, the multi-value data may be converted into two-value data, so that the quantity of information can be similarly curtailed. In
15 this way, similarly to at step ST503, by presetting a specific rule of data conversion process in every image type, it is possible to convert into efficient image data. In this case, unlike step ST503, without processing data conversion in every rectangular region,
20 since the same process is applied on the entire image, the processing speed is higher.

As a result of data conversion process, similarly to at step ST503, converted image data 162 is output.

In the case of indiscriminative original at step
25 ST501, without processing data conversion by using the information of the pixel attribute obtained in the region discriminating unit 102, the input image data is

directly output as corrected image data (step ST505).
Meanwhile, the data conversion process (step ST503 and
step ST504) is not limited to processing of input image
data such as change of resolution, compression rate and
5 number of color, but also includes, as mentioned above,
the process of converting the attribute region
information into image data.

Thus, since the data conversion is processed
according to the determined type of the image data by
10 determining the type of the input image data from the
result of discriminating the region, it is possible
to convert into efficient image data having less
deterioration of image quality.

<Second Embodiment>

15 A second embodiment of the present invention is
described next. The second embodiment is shown in
FIG. 6, and relates to an image processing apparatus
for correcting image data by appropriate density
conversion or filter processing, according to the
20 result of discriminating the type of image.

FIG. 6 schematically shows the constitution of the
image processing apparatus of the second embodiment.
In FIG. 6, the image processing apparatus comprises an
image input unit 101, a region discriminating unit 102,
25 an image type determining unit 103, an image correcting
unit 106, and an image forming unit 105, in which the
image correcting unit 106 corresponds to the data

converting unit 104 in the first embodiment shown
in FIG. 1. The image input unit 102, region
discriminating unit 102, image type determining unit
103, and image forming unit 105 are already explained,
5 and the image correcting unit 106 is described below.

FIG. 7 is a flowchart showing an example of
document processing procedure in the image processing
apparatus shown in FIG. 6. Of the flowchart of the
constitution in FIG. 1 shown in FIG. 2, herein, the
10 data conversion process (step ST205) is changed to
image correction process (step ST207).

After determining the document type of the image
data input in the image type determining unit 103, in
the image correcting unit 106, the image data is
15 corrected by appropriate density conversion or filter
processing according to the document type corresponding
to the type of the image data (step ST207).

FIG. 8 is a flowchart showing the detail of image
correction process as an example in the image
20 correcting unit 106, which is a flowchart of the
process corresponding to step ST207 shown in FIG. 7.

The image type information 161 is the output of
the image type determining unit 103, and expresses the
type of input image data, which is one of dot photo
25 original 153, dot background original 154, continuous
gradation photo original 155, uniform background
original 156, rectangle discriminative original 157,

and indiscriminative original 158.

First, it is checked if the image type information 161 is an indiscriminative original or not (step ST601). If not indiscriminative original, next it is checked if
5 rectangle discriminative original or not (step ST602). In the case of rectangle discriminative original, making use of the information of the pixel attribute obtained in the region discriminating unit 102, the image correction process is executed on the input image
10 data in every rectangular region (step ST603).

Image correction process is, for example, density conversion process or filtering process. A rule of image correction process may be preset in every pixel attribute, and the image correction process may be done
15 according to this rule. For example, in the case of character region, high pass filter may be processed so that the characters may be more clear, or in the case of dot photo region, low pass filter may be processed to obtain a smooth image without moiré. As a result,
20 being corrected into image data of high quality, it may be output as corrected image data 163. In this way, by presetting a specific rule of image correction process in every pixel attribute, it is possible to correct
25 into image data of high quality.

If it is not rectangle discriminative original at step ST602, the entire image is uniformly processed by image correction (step ST604). As uniform image

correction process, for example, in the case of uniform background original, the entire image may be processed by high pass filter so that the characters may be clear, or in the case of dot photo region, the entire image
5 may be processed by low pass filter to obtain a smooth image without moiré. In this way, similarly to at step ST603, by presetting a specific rule of image correction process in every image type, it is possible to correct into image data of high quality. In this
10 case, unlike step ST603, without processing image correction in every rectangular region, since the same process is applied on the entire image, the processing speed is higher. As a result of image correction process, similarly to at step ST603, corrected image
15 data 163 is output.

In the case of indiscriminative original at step ST601, without processing image correction by using the information of the pixel attribute obtained in the region discriminating unit 102, the input image data is
20 directly output as corrected image data (step ST605).

Thus, since the image correction is processed according to the determined type of the image data by determining the type of the input image data from the result of discriminating the region, it is possible to
25 obtain image data of high quality.

<Third Embodiment>

A third embodiment of the present invention is

described below. The third embodiment is shown in FIG. 9, and relates to an image processing apparatus for selecting the image format to be stored, converting into this format, and storing, according to the result of discriminating the type of image when filing the image.

FIG. 9 schematically shows the constitution of the image processing apparatus of the third embodiment. In FIG. 9, the image processing apparatus comprises an image input unit 101, a region discriminating unit 102, an image type determining unit 103, an image format changing unit 107, and an image forming unit 105, in which the image format changing unit 107 corresponds to the data converting unit 104 and an image memory unit 108 corresponds to the image forming unit 105 in the first embodiment shown in FIG. 1. The image input unit 102, region discriminating unit 101, and image type determining unit 103 are already explained and are omitted herein. An image memory unit 108 is the output destination after conversion of image format, and is substantially regarded to operate same as the image forming unit 105. Therefore, the image format changing unit 107 is described below.

FIG. 10 is a flowchart showing an example of document processing procedure in the image processing apparatus shown in FIG. 9. Of the flowchart of the constitution in FIG. 1 shown in FIG. 2, herein, the

data conversion process (step ST205) is changed to image format changing process (step ST208).

After determining the document type of the image data input in the image type determining unit 103, in the image format changing unit 107, the image format suited to be stored in the image memory unit 108 is selected according to the document type corresponding to the type of the image data, and it is converted to this format (step ST208).

FIG. 11 is a flowchart showing the detail of image format conversion process as an example in the image format changing unit 107, which is a flowchart of the process corresponding to step ST208 shown in FIG. 10.

The image type information 161 is the output of the image type determining unit 103, and expresses the type of input image data, which is one of dot photo original 153, dot background original 154, continuous gradation photo original 155, uniform background original 156, rectangle discriminative original 157, and indiscriminative original 158.

First, it is checked if the image type information 161 is an indiscriminative original or not (step ST701). If not indiscriminative original, next it is checked if rectangle discriminative original or not (step ST702).

In the case of rectangle discriminative original, making use of the information of the pixel attribute obtained in the region discriminating unit 102, the

image format conversion process is executed on the input image data in every rectangular region (step ST703).

5 The image format includes, for example, JPEG
format and TIFF (G4) format. A rule of image format
conversion process may be preset in every pixel
attribute, and the image format conversion process may
be done according to this rule. For example, in the
case of character region, the quantity of data can be
10 curtailed by converting into the TIFF (G4) format, and
it is changed into efficient image data. Or, in the
case of dot photo region or continuous gradation photo
region, by converting into the JPEG format, the
quantity of data can be compressed while suppressing
15 deterioration of image quality, and in this case, too,
it is changed into efficient image data. As a result,
it can be stored as format converted image data 164.
In this case, from one image data, plural formats of
image data are generated. When storing, therefore,
20 they may be stored individually. At this time, the
structure of the original image data and the format
converted image data name generated therefrom may be
saved as reference file, and when restoring, by
referring to this reference file, the original image
25 data may be reconstructed from the format converted
image data 164. In this way, by presetting a specific
rule of image format conversion process in every pixel

attribute, it is possible to convert into image data format of high efficiency by curtailing the quantity of data.

5 If it is not rectangle discriminative original at step ST702, the entire image is uniformly processed by image format conversion (step ST704). As uniform image format conversion process, for example, in the case of uniform background original, which does not include photograph, by converting into TIFF (G4) format, the
10 quantity of data can be curtailed, or in the case of dot photo original or continuous gradation photo original, by converting into the JPEG format, the quantity of data can be compressed while suppressing deterioration of image quality. In this way, similarly
15 to at step ST703, by presetting a specific rule of image format conversion process in every image type, it is possible to convert into image data format of high efficiency reduced in the quantity of data. In this case, unlike step ST703, without processing image
20 format conversion in every rectangular region, since the same process is applied on the entire image, the processing speed of image format conversion is higher, and plural image formats are not generated, and therefore the reference file is not needed, and the
25 original image data can e restored at high speed from the stored format converted image data. As a result of image format conversion process, similarly to at

step ST703, it can be stored as format converted image data 164.

In the case of indiscriminative original at step ST701, without processing image format conversion by
5 using the information of the pixel attribute obtained in the region discriminating unit 102, the input image data is directly output as format converted image data (step ST705).

Thus, since the image format conversion is
10 processed according to the determined type of the image data by determining the type of the input image data from the result of discriminating the region, it is possible to change into image data of high efficiency, and the quantity of information when storing can be
15 curtailed.

<Fourth Embodiment>

A fourth embodiment of the present invention is described below. The fourth embodiment is shown in FIG. 12, and relates to an image processing apparatus
20 for selecting the application to be started, determining the starting parameter, and starting the application, according to the result of determining the type of the image.

FIG. 12 schematically shows the constitution of
25 the image processing apparatus of the fourth embodiment. In FIG. 12, the image processing apparatus comprises an image input unit 101, a region discriminating unit 102,

an image type determining unit 103, an application
starting unit 109, and an application processing result
forming unit 110, in which the application starting
unit 109 corresponds to the data converting unit 104
5 and the application processing result forming unit 110
corresponds to the image forming unit 105 in the first
embodiment shown in FIG. 1. The image input unit 101,
region discriminating unit 102, and image type
determining unit 103 are already explained and are
10 omitted herein. The application processing result
forming unit 110 is the output destination of the
result of processing after starting the application,
and is substantially regarded to operate same as the
image forming unit 105. Therefore, the application
15 starting unit 109 is described below.

FIG. 13 is a flowchart showing an example of
document processing procedure in the image processing
apparatus shown in FIG. 12. Of the flowchart of the
constitution in FIG. 1 shown in FIG. 2, herein, the
20 data conversion process (step ST205) is changed to
application starting process (step ST209) and the image
forming process (step ST206) is changed to application
processing result forming process (step ST210).

After determining the document type of the image
25 data input in the image type determining unit 103, in
the application starting unit 109, an application
suited to image processing according to the type of the

document corresponding to the type of the image data is selected, the starting parameter is determined, and the application is started (step ST209).

FIG. 14 is a flowchart showing the detail of application starting process as an example in the application starting unit 109, which is a flowchart of the process corresponding to step ST209 shown in FIG. 13.

The image type information 161 is the output of the image type determining unit 103, and expresses the type of input image data, which is one of dot photo original 153, dot background original 154, continuous gradation photo original 155, uniform background original 156, rectangle discriminative original 157, and indiscriminative original 158.

First, it is checked if the image type information 161 is an indiscriminative original or not (step ST801). If not indiscriminative original, next it is checked if rectangle discriminative original or not (step ST802). In the case of rectangle discriminative original, making use of the information of the pixel attribute obtained in the region discriminating unit 102, the application is started on the input image data in every rectangular region, and various image processings are done (step ST803).

The application includes, for example, image filing, printing, facsimile transmission, layout

understanding, character recognition, rule extraction and other image processings. A rule of application for starting may be preset in every pixel attribute, and the application starting process may be done according to this rule. For example, in the case of character region, by layout understanding, the column setting or other document structure may be recognized, and the characters may be encoded by character recognition. Or, in the case of dot photo region or continuous gradation photo region, the image filing may be started in order to save the image, or when printing, if the region is color, by attaching a starting parameter of color, the printer at the output destination may be automatically changed to a color printer. The result processed by the application is the application processing result data 165, which may be provided in various formats such as printout, file, or character recognition result. By thus presetting the rule of application starting process in every pixel attribute, as soon as the image data is input, various processings may be done automatically.

If it is not rectangle discriminative original at step ST802, the entire image is uniformly processed by starting the application (step ST804). As uniform image format conversion process, for example, in the case of uniform background original, which does not include photograph, by layout understanding, the

document structure such as paragraph is recognized, and the character can be encoded by character recognition, or in the case of dot photo original or continuous gradation photo original, the image filing may be
5 started for saving the image, or printing or facsimile transmission can be done directly. The result of processing by the application is, similarly to at step ST803, it is the application process result data 165, and various formats may be provided, such as printout,
10 file and character recognition result.

In the case of indiscriminative original at step ST801, without application starting process by using the information of the pixel attribute obtained in the region discriminating unit 102, the input image data is
15 directly output as application process result data, or by starting the image filing or the like, the image data is directly stored as file, and the processing may be selected later by the determination of the user (step ST805).

20 Thus, since the application for processing the image is started according to the determined type of the image data by determining the type of the input image data from the result of discriminating the region, it is possible to perform various processes as soon as
25 the image data is input, so that the labor may be saved.

As described herein, the image processing apparatus of the present invention is designed to

incorporate a document image through an image input unit 101, extract one physically or logically coupled from the status of data of each pixel and adjacent pixels in the region discriminating unit 102 as one
5 region, measure the feature quantities such as position, size, shape, structure and density distribution of each region on the image, and discriminate the measured result as a region having the attribute such as character, photograph, dot or the like as the document
10 constituent element according to a predetermined rule. On the basis of the attribute information or the like, the type of the document depending on the type of the image data is determined from the feature such as complicatedness of the entire document image input in
15 the image type determining unit 103, and the image data format is converted in the data converting unit 104 depending on the type of the document corresponding to the type of the image data.

In the image correcting unit 106, by processing to
20 correct the image data by adequate density conversion or filter processing according to the type of the document corresponding to the type of the image data, in the image format changing unit 107, the image format suited to be stored in the image memory 108 is selected
25 according to the document type corresponding to the type of the image data, and it is processed to be converted into this format.

Further, in the application starting unit 109, selecting an application suited to image processing according to the type of the document corresponding to the type of the image data, the starting parameter is
5 determined, and it is made possible to process to start the application.

Therefore, in the original image data input in the apparatus, by extracting the region by distinguishing the different document elements such as character,
10 photograph, drawing, table, and dot, the feature quantities such as presence or absence of key region such as dot and photograph, and complicatedness as document structure from the degree of overlapping of rectangular region are determined, and hence it is
15 possible to determine what kind of document is the input image data, and by making use of the determining result, it is possible to convert into efficient image data less in deterioration of image quality, or correct image in order to obtain image data of high quality.

20 When saving as image file, the format suited to the image data can be selected automatically, and efficient filing is realized.

Further, as soon as the document image data is input, the image processing application is selected and
25 started automatically, so that the labor is saved.

Further, as other embodiments relating to the image processing apparatus, image forming apparatus,

and image processing method of the present invention, fifth to twelfth embodiments are described specifically below while referring to the accompanying drawings.

<Fifth Embodiment>

5 A fifth embodiment is shown in FIG. 15, which presents an image forming apparatus for composing an image quality parameter as shown in FIG. 15, in addition to the first embodiment. An electronic copier usually comprises an image input unit such as scanner, 10 an image processing unit, and an image forming unit such as printer. The electronic copier also includes an operation unit (control panel) to be used by the user for making various settings. The operation unit has an image quality parameter input unit as described 15 later, and an image quality adjusting parameter is input according to the user's preference of image quality.

That is, in FIG. 15, the image forming apparatus comprises an image input unit 1, a page information 20 discriminating unit 2, an image processing unit 3, and an image forming unit 4. The image forming apparatus is connected with an image parameter input unit 31 for inputting an image quality adjusting parameter according to the user's preference of image quality, an 25 image quality storing unit 32 for storing the image quality parameter input by the image quality parameter input unit 31, and an image quality parameter deciding

unit 33 for deciding the image quality parameter to be processed in the image processing unit 3 on the basis of the image quality parameter stored in the image quality parameter storing unit 32.

5 Referring to FIG. 15, the embodiment of the present invention is described in detail below.

First, the image input unit 1 is, for example, a color CCD scanner, which reads the original color image, and separates into electric signals of three primaries, R (red), G (green), B (blue), vertically and horizontally, converts into 8-bit digital data of each color in each unit pixel (for example, 400 dpi), and outputs as R, G, B, respectively.

Image signals of R, G, B are input into the page information discriminating unit 2 for discriminating the type of the entire image, and the image processing unit 3.

FIG. 16 shows an example of the image processing unit 3, which is composed of a color converting unit 51, a space filter 52, a black color unit 53, a γ -correction unit 54, and a gradation processing unit 55, and in each block the page information output by the page information discriminating unit 2 is input together with the image signals output by all blocks.

25 In the color converting unit 51, signals of R, G, B input from the scanner are converted in the following formula 1, and signals of C (cyan), M (magenta), and Y

(yellow) corresponding to the signals of the image forming unit 4 are obtained.

$$Dr = -\log R$$

$$Dg = -\log G$$

5 $Db = -\log B$

$$\begin{pmatrix} C \\ M \\ Y \end{pmatrix} = \begin{pmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ a_{31} & a_{32} & a_{33} \end{pmatrix} \begin{pmatrix} Dr \\ Dg \\ Db \end{pmatrix}$$

This operation is composed of the circuit shown in FIG. 17. The color converting unit 51 is composed of
10 look-up tables (LUT) 61a to 61c for log conversion, nine multipliers 62a to 62i for 3×3 matrix operation, and three adders 63a to 63c.

In the color converting unit 51, the method of use of page discrimination signal is, for example, as
15 follows. First, as the types of original image data mentioned in the first embodiment, or the types of individual documents (called page discrimination information hereinafter), uniform background (having characters), dot background (having characters), dot
20 photo (having photo only), and continuous photo (having photo only) are defined. In these four types of images, generally, it is known that the blue color is strong in the case of continuous photo using photographic printing paper. It is therefore preferred to change
25 the color reproducibility only in the case of continuous photo. To change the color reproducibility, it is necessary to change the coefficients a_{11} to a_{33}

of the color conversion matrix. That is, preparing
coefficients all to a33 for continuous photo, and
coefficients all to a33 for other image, they are
changed over on the basis of the page discrimination
5 information.

The space filter 52 is composed of, for example, a
high frequency component calculating unit 71, a
multiplier 72 for operating the weight of high
frequency component, and a subtracting unit 73 of the
10 original image as shown in FIG. 18. The high frequency
component calculating unit 71 is to operate, for
example, 3×3 Laplacian filter, and emphasize the high
frequency component of the original image, and it is
composed of a filter as shown in FIG. 19.

15 FIG. 20 shows a specific example of circuit
constitution of the space filter 52, in which the high
frequency component calculating unit 71 is composed of
flip-flop circuits 71a to 71f, multipliers 71g to 71p,
and adder 71q. This circuit is required for each color
20 of C, M and Y. Herein, the weighting coefficient K is
an image quality parameter determined by the image
quality parameter deciding unit 33, and by adjusting
this weighting coefficient K, the sharpness of image
can be adjusted.

25 The method of using the page discrimination
information in this space filter 52 is the method of
changing the filter coefficient or weighting

coefficient K on the basis of the page discrimination information shown in FIG. 19. For example, in the case of uniform background or continuous photo, the filter weighting coefficient K is large, and in the case of dot background or dot photo, the weighting coefficient K is set smaller in order to suppress dot moiré.

The black color unit 53 processes to generate signal of C (cyan), M (magenta), Y (yellow), and K (black) from the signals of C (cyan), M (magenta), and Y (yellow), and, for example, the UCR processing is done as shown in the formula below.

$$K = a \times mn (C, N, Y)$$

$$C' = C - K$$

$$M' = M - K$$

$$Y' = Y - K$$

a: parameter for determining the amount of black color

This operation is composed of, for example, the circuit shown in FIG. 21. This circuit is composed of comparators 81a, 81b, selectors 82a, 82b, and subtractors 83a to 83c.

The method of utilizing page discrimination in the black color unit 53 is, for example, a method of changing the black color rate (a) in every type of image. In the uniform background or dot background having characters, by setting the black color rate (a) higher, black characters are reproduced more easily in

a single black color, and the character reproducibility is enhanced. In the case of dot photo or continuous photo, the color reproducibility is improved by setting the black color rate (a) lower.

5 The γ -correction unit 54 is a block used for correcting the density characteristic of the printer unit of each color of C, M, Y, and adjusting the density by the user, and a simplest constitution is a look-up table (LUT) 90 of input of 8 bits and output of
10 8 bits as shown in FIG. 22. In this table, for example, a density conversion curve as shown in FIG. 23 is set. The default is, for example, a curve of 0 (a curve equal in input and output), and when the user adjusts the density, a density curve corresponding to -3 to +3
15 is selected and set according to the determined image quality parameter.

 In the γ -correction unit 54, the following setting method using page discrimination information is available. For example, in the case of uniform
20 background or dot background having characters, as the γ -curve used as γ -correction, a high- γ table is prepared and set. As a result, the reproducibility of characters is enhanced. On the other hand, in the case of dot photo or continuous photo, a table of linear
25 input and output is set for improving the gradation reproducibility.

 The gradation processing unit 55 is to process to

convert 8-bit signal of C, M, Y, K into, for example, 1 bit (binary), and the error diffusion method is known as a representative method.

5 In the error diffusion method, a binary error of an already binary peripheral pixel is multiplied by a certain weighting coefficient, and this product is added to the density of the pixel of notice, and a binary value is obtained by fixed threshold. FIG. 24 is a structural block diagram of binary process by error diffusion method. In FIG. 24, the binary circuit includes an input image signal 40, a correcting unit 41 for correcting image information of pixel of notice, a corrected image signal 411, a binary unit 42 for obtaining a binary value from the corrected image information of pixel of notice, a binary image signal 421, a binary error calculating unit 43 for calculating the binary error of binary pixel of notice, a binary error signal 431, a weighting coefficient memory unit 44 for storing the weighting coefficient for calculating the weighting error, a weighting error calculating unit 45 for calculating a weighting error by multiplying the binary error calculated in the binary error calculating unit 43 by the weighting coefficient of the weighting error memory unit 44, a weighting error signal 451, an error memory unit 46 for storing the weighting error calculated in the weighting error calculating unit 45, and an image correction

10

15

20

25

signal 461. The binary process of the error diffusion method is described in detail below.

The input image signal 40 of the γ -correction unit 55 is corrected by the image correction signal 461 described later, and a corrected image signal 411 is output. The corrected image signal 411 is compared with a binary threshold Th (for example, in 80h, "h" denotes hexadecimal notation) in the binary unit 42, and when the corrected image signal 411 is larger than the binary threshold Th, "1" (black pixel) is output as binary image signal 421, and "0" (white pixel) is output when smaller. In the binary error calculating unit 43, the difference between the corrected image signal 411 and binary image signal 421 (herein, however, it is 0h when binary image signal is "0", and ffh when "1") is calculated, and it is output as binary error signal 431. In the weighting error calculating unit 45, the binary error signal 431 is multiplied by the weighting coefficients A, B, C, D ($A=7/16$, $B=1/16$, $C=5/16$, $D=3/16$) of the weighting coefficient memory unit 44, and the weighting error 451 is calculated. Herein, the * mark in the weighting coefficient memory unit 44 indicates the position of pixel of notice, and the binary error of the pixel of notice is multiplied by the weighting coefficients A, B, C, D, and the weighting error of four peripheral pixels of the pixel of notice (pixels corresponding to the positions of the

weighting coefficients A, B, C, D) is calculated. The error memory unit 46 is to store the weighting error 451 calculated in the weighting error calculating unit 45, and the weighting errors of four pixels calculated in the weighting error calculating unit are added and stored in the regions of eA, eB, eC, eD corresponding to the pixel of notice *. The image correction signal 461 is a signal at position of *, and is a cumulative signal of weighting errors of four pixels calculated in the above procedure.

In the above explanation of gradation processing unit 55, the output is binary, but by preparing a plurality of binary thresholds Th and comparing with the input image signal, multi-value processing is same as in binary value.

In the gradation processing unit 55, for example, the page discrimination information is utilized as described below. First, FIGS. 25A and 25B show two cases of output of the gradation processing unit 55.

In FIG. 25A, the laser modulator, not shown, of the image forming unit 4 is modulated in the unit of two pixels, and as determined from the diagram, the resolution is $1/2$, but since the pixel size is small even at the same gradation level, the gradation output withstands fluctuation of recording, and an image can be formed on the basis of a stable output.

In FIG. 25B, on the other hand, the laser is

driven in the unit of one pixel, and the resolution is high although stability of density fluctuation is insufficient. That is, the one-pixel modulation method of high resolution is employed in the case of uniform background or dot background having characters, and the two-pixel modulation method of high density stability is employed in the case of dot photo or continuous photo.

Examples of use of page discrimination information in each process are presented herein, but the method of use is not limited to these examples alone, but various methods may be considered.

So far is shown an example of structure of the image processing unit 3, and thus processed signals of C (cyan), M (magenta), Y (yellow), and K (black) are input in the image forming unit 4, and an image is formed and output on a paper.

In such constitution, an embodiment of the page information discriminating unit 2 in the fifth embodiment operating same as in the first embodiment is described below.

FIG. 26 shows an example of structure of the page information discriminating unit 2. The page information discriminating unit 2 is composed of region discriminating unit 102 and original type determining unit 103 shown in FIG. 1.

The page information discriminating means 2 takes

in a document image, in the region discriminating means
21, one coupled physically or logically from the
situation of each pixel and vicinal pixel data is
extracted as one region, feature quantities of each
5 region such as position on the image, size, shape,
structure, and density distribution are measured, and
the result of measurement is discriminated as the
region having attribute such as character, photograph,
and dot as the document constituent elements according
10 to a preset rule. On the basis of the attribute
information and others, in the original type
determining unit 103, the type of the document is
decided from the features of the entire input document
image, and the image data format can be converted
15 according to the type of the document.

The structure and operation of the region
discriminating unit 102 and original type determining
unit 103 are same as in the first embodiment shown in
FIG. 1 and after, and their description is omitted
20 herein.

<Sixth Embodiment>

The foregoing description relates to an example of
using the page discrimination information only when
determining the processing conditions in each process
25 of the image processing unit, but in a sixth embodiment
shown in FIG. 27, rectangle discrimination information
(image type of plural regions) is used together with

the page discrimination information.

In FIG. 27, the page discrimination information and rectangle discrimination information are used as the processing conditions in each process of the image processing unit. As compared with the constitution in FIG. 15, a region discriminating unit 6 is added, and together with the page discrimination information output by the page information discriminating unit 2, the rectangle discrimination information output by the region discriminating unit 6 is input into the image processing unit 7. By using both page discrimination information and rectangle discrimination information, more specific parameter setting is possible in the image processing unit 7.

For example, the page discrimination information is the information shown in FIG. 28A. Herein, "0. Region discrimination" shows that the rectangle discrimination information output by type region discriminating unit 6 is valid, and "1. Uniform background to 4. Continuous photo" means that the page discrimination information output by the page information discriminating unit 2 is valid.

When the page discrimination information is "0. Region discrimination," using the discrimination result of the rectangle unit of the region discriminating unit 3, the image processing condition is changed in the rectangle unit in the image processing unit 3. On the

other hand, when the page discrimination information is "1. Uniform background to 4. Continuous photo," this information is used as the discrimination information in the page unit, and the image processing unit 4 sets the image processing condition on the basis of this information, and executes a specific processing in the image unit. Thus, by using the page discrimination information, as compared with the conventional image copying apparatus generally having five operation modes shown in FIG. 28B as the operation modes (operation modes corresponding to the type of the original to be copied), an automatic mode can be provided as shown in FIG. 28C (the mode for selecting a mode for executing specific process image unit and a mode for executing the process by changing the processing condition in the unit of rectangle or pixel, automatically on the basis of the page discrimination information and outputting), so that an image of a higher image quality than in character/photo mode can be obtained.

When the page discrimination information is "5. Indiscriminative," it means all of "0. Region discrimination to 4. Continuous photo" are invalid, and none of the discrimination information can be used. Therefore, in the image processing unit 7, specific processing is done in the entire image without using discrimination information, or the type of image discriminated in the pixel unit in a method explained

below, and the image is processed.

<Seventh Embodiment>

A seventh embodiment is shown in FIG. 29, in which the discrimination process in pixel unit is further
5 added to the first embodiment. FIG. 29 shows an example of structure of an image processing unit 7 when executing image processing by discriminating in the pixel unit.

The image processing unit 7 shown in FIG. 29 is
10 similar to the image processing unit 3 for inputting page discrimination information shown in FIG. 16, except that a pixel unit discriminating unit 56 is added. In the constitution in FIG. 16, specific page discrimination information for entire image is input in
15 the color converting unit 51 to gradation processing unit 55, and each image processing is determined in the image processing condition on the basis of its page discrimination information. In the constitution of the image processing unit 7 in FIG. 29, instead of the page
20 discrimination information, the pixel unit discriminating unit 56 discriminates the type of image in the pixel unit on the basis of the input image information, and processes by setting the image processing condition in each image processing block on
25 the basis of this discrimination information.

The processing method in the pixel unit discriminating unit 56 includes, for example, a method

of separating three regions of character, photo, and dot photo, as disclosed in "Block Separate Transformation Method (BSET)" in "Discrimination Processing Method of Dot Photograph" (J. of Japan Society of Electronics, Information Communication, Vol. 5 J70-B, No. 2, February 1987).

In this method, the object image is divided into blocks, and three regions are separated by density change within blocks. At this time, it is intended to make use of nature of density changes, that is:

- Photograph is small in density change in block.
- Character and dot photograph are large in density change in block.
- Character is large in period of density change.
- 15 - Dot photograph is small in period of density change.

The detail is described below.

- (1) The object image is divided into blocks of $(m \times n)$ pixels.
- 20 (2) Maximum density signal D_{\max} and minimum density signal D_{\min} in block are determined, and maximum density difference signal ΔD_{\max} in block is calculated.
- (3) Comparing preset threshold $Th1$ and ΔD_{\max} ,
25 photo region and non-photo resin (character and dot photo region) are separated in the following condition.

$\Delta D_{\max} \leq Th1$ Photo region

$\Delta d_{\max} > Th1$ Non-photo region

(4) Each pixel in block is coded into binary signal (0/1) by average signal D_a of signal in block.

(5) The number of times of 0/1 change K_h between
5 pixels consecutive in the main running direction in
block is determined. Similarly, in the sub-scanning
direction, the number of times of changes K_v is
determined.

(6) Comparing preset threshold $Th2$ and K_h and K_v ,
10 the character region and dot photo region are separated
in the following condition.

$K_h \geq Th2$ and $K_v \geq Th2$ Dot photo region

$K_h < Th2$ and $K_v < Th2$ Character region

In this procedure, the character, photo, and dot
15 photo regions can be separated.

FIG. 30 shows an example of circuit configuration
of pixel unit discriminating unit 56, which is a
circuit for calculating the maximum density difference
 ΔD_{\max} in 4×4 window (shaded areas showing pixel of
20 notice) shown in FIG. 31. This circuit is composed of
selector 12a, comparators 12b to 12g, and subtractor
12h.

<Eighth Embodiment>

An eighth embodiment is shown in FIG. 32, in
25 which a case of setting the processing condition of
pixel unit discriminating unit 56 by using page
discrimination information is explained, and this is an

effective method for enhancing the precision of discrimination.

FIG. 32 shows a constitution of using page discrimination information in the pixel unit discriminating unit 8. The operation of the page information discriminating unit 2 is as explained already, and the pixel unit discriminating unit 8 receives the page discrimination information together with the input image data of the image input unit 1, and sets a parameter for discrimination on the basis of the page discrimination information.

First, as page discrimination information, four pieces of information shown in FIG. 28D are output, and a discriminating method of pixel unit is explained in a case of discriminating the character region by using the maximum density difference ΔD_{max} . When using the maximum density difference ΔD_{max} , it is known that separation into dot region and character region is difficult. Therefore, using page discrimination information, it is set at threshold $Th=th1$ in the uniform background region, at $Th=th2$ in the dot photo region, and $Th=th3$ in the dot photo and continuous photo region (where $th1>th2>th3 \cong 0$). By thus setting, the photo region is not falsely discriminated as character region, and characters in the dot background region which are difficult to discriminate can be lowered in the rate of false discrimination in the

non-character region, so that very effective pixel unit discrimination may be realized.

<Ninth Embodiment>

5 A ninth embodiment is shown in FIGS. 28A and 29,
in which the duration of time necessary for
discriminating process is evaluated by using "Time
over" prepared as page discrimination information, and
it is decided whether or not to use the page
discrimination information according to the result.
10 Thus, the certainty of region recognition can be
attained as far as possible in the range of processing
time.

That is, in FIG. 28A, "6. Time over" is provided
as page discrimination information. The original type
15 discriminating unit 22 shown in FIG. 26 is more
preferably realized by the software, and therefore the
processing time differs depending on the type of the
original to be input. Therefore, the discriminating
process may not be terminated within the required
20 processing time of the image forming apparatus. This
page discrimination information "6. Time over" is, by
measuring the time required for discriminating process,
set when it is not terminated within the processing
time specified in this system. In such a case, the
25 image processing unit 7 discriminates in the pixel unit
without using page discrimination information as
explained already in, for example, FIG. 29, and

processes the images according to this discrimination information, thereby finishing within the preset range of processing time.

<Tenth Embodiment>

5 A tenth embodiment is shown in FIG. 33, and using "Indiscriminative" prepared as page information similarly, it is designed to evaluate the discrimination precision of discriminating process, and execute discriminating process appropriately according to it.

10 That is, the original type discriminating unit 22 outputs information such as "5. Indiscriminative" as shown in FIG. 28A. It corresponds to the flow of discriminating process at step ST403 in FIG. 4.

FIG. 33 shows a constitution of this embodiment.

15 The image forming apparatus in FIG. 33 comprises an image input unit 1, a page information discriminating unit 2, an image dividing unit 10, a region discriminating unit 11, a discrimination precision determining unit 12, a selecting unit 13, an
20 image processing unit 14, and an image forming unit 4.

 In this constitution, when the discrimination precision is poor, it is determined to be indiscriminative, and in such a case, therefore, the image processing unit 14 or 19 discriminates the pixel
25 unit without using page discrimination information as explained already, for example, in FIG. 29, and it is possible to process images on the basis of this

discrimination information. In this way, effects of poor discrimination result of discrimination precision can be avoided, and processing result of a specific level may be maintained.

5 <Eleventh Embodiment>

 An eleventh embodiment is shown in FIG. 34, and using "Indiscriminative" prepared as page information similarly, it is designed to evaluate the complicatedness of discriminating process, and execute
10 discriminating process appropriately according to it.

 FIG. 34 shows a constitution of this embodiment.

 The image forming apparatus in FIG. 34 comprises an image input unit 1, a page information discriminating unit 2, a complicatedness determining unit 15,
15 an image dividing unit 16, a region discriminating unit 17, a selecting unit 18, an image processing unit 19, and an image forming unit 4.

 In this constitution, when the complicatedness of the object image is very high, it is determined to be
20 indiscriminative, and in such a case, therefore, the image processing unit 14 or 19 discriminates the pixel unit without using page discrimination information as explained already, for example, in FIG. 29, and it is possible to process images on the basis of this
25 discrimination information. In this way, adverse effects of discrimination result when the complicatedness is high can be avoided, and processing

result of a specific level may be maintained.

The foregoing embodiments are representative methods using the page discrimination information, and a further different embodiment is shown in FIG. 35.

5 <Twelfth Embodiment>

 A twelfth embodiment is shown in FIG. 35, in which the image is processed preliminarily by plural types of image processing conditions depending on the image information, if obtained without waiting for output of
10 the discrimination result of page information in order to increase the processing speed, it is stored in the memory region, and when the discrimination result is obtained, the result of image processing corresponding to it is read out from the memory region. Thus, by
15 parallel operation of discriminating process of image type and image processing of plural types, the processing speed can be increased on the whole.

 The image forming apparatus in FIG. 35 comprises an image input unit 1, a page information discriminating unit 2, image processing units 25, 26, a
20 storing/reading unit 27, a memory unit 28, and an image forming unit 4. This constitution has two image processing units 25, 26, and memory unit 28 for saving the processing results output by the image processing
25 units 25, 26, and it is designed to output the image by selecting and reading from the stored plural image processing results by the page information

discriminating unit 2.

In the image processing unit 25 and image processing unit 26, it is designed to process by two kinds of image processing conditions regardless of the page discrimination information, for example, the image processing parameter suited to character image and image processing parameter suited to photo image. The two kinds of image processing results are stored in the memory unit 28, for example, memory or HDD, and when the processing result output by the page information memory unit 2 is uniform background or dot background, the image processing result for character processed by the image processing unit 25 is read out from the storing/reading unit 27, and on the other hand, when the page information output by the page information discriminating unit 2 is dot photo or continuous photo, the image processing result for photo processed by the image processing unit 26 is read out from the memory unit 28 and output.

In such constitution, it is possible to operate processing of the page information discriminating unit 2 and processing of the image processing units 25, 26 parallel (that is, image processing is done in the image processing units 25, 26 without waiting for output of the page information discriminating unit 2), so that high speed operation is possible in the image forming apparatus.

As explained already, the image processing unit 3 shown in FIG. 15 makes use of the page discrimination information used in each image processing shown in FIG. 16, and the relation between the original mode showing the operation mode of the apparatus and the processing condition of page discrimination information and each image processing block is shown in FIG. 36.

In FIG. 36, the page discrimination result shows the page discrimination information shown in FIG. 28A, such as character/photo, character, map, printed photo, and photo in photographic printing paper shows the processing condition of each image processing such as color conversion, background processing, ..., gradation processing, and it means the same condition as when each is selected as the original mode. The processing condition of each image processing for the same page discrimination information is not always the same, and symbols such as A, B, ... denote variations of parameters slightly different from the case when selected as original mode, and it is necessary to divide into proper groups or into further small divisions depending on the image processing.

As explained herein, according to the embodiments of the present invention, if character and photograph are mixed, the character/photo mode is selected as the original mode, and the region or entire image is automatically discriminated as one category, and the

image processing is done so as to obtain the optimum image quality.

Further, in discrimination done by the apparatus in the character/photo mode, not only the discrimination of the region but also discrimination
5 information of entire image are output, and therefore the recognition precision can be enhanced, so that deterioration of image quality due to wrong recognition of type of image can be suppressed.

Further, to decrease the problems of such wrong
10 recognition, such process as to decrease the difference in processing between categories to be discriminated (for example, character and photo) and make the deterioration of image quality due to wrong recognition
15 less obvious even when discriminated falsely, and an output of higher image quality can be obtained as compared with the prior art.

As described specifically herein, the present invention presents an image processing apparatus
20 capable of suppressing deterioration of image quality due to wrong discrimination in region discrimination, and an image forming apparatus and an image processing method capable of forming an image at high quality by processing appropriately depending on the type of the
25 image data.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore,

the invention in its broader aspects is not limited to
the specific details and representative embodiments
shown and described herein. Accordingly, various
modifications may be made without departing from the
5 spirit or scope of the general inventive concept as
defined by the appended claims and their equivalents.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
22